

*Valves make the difference*

**MV2-Microvalve Comparison**

Features	Microvalve	MV2	MV2 Benefits
<b>Construction/Design</b>			
Body	Aluminum	Carbon Steel	
Base/Nipple	Carbon steel	High strength steel	
Bolt holes	Normal	Isolated	
Internal bypass line	No	Yes	
Knob	Pin fastened	Integrated	
Media connection	1-1/4 female thread	1-1/4 male thread	
<b>Metering/Abrasive Flow</b>			
Abrasive flow rate	Normal	High	Flows more abrasive (up to twice depending on type of abrasive)
Virtual Position Indicator (VPI)	No	Yes	Simplifies setting and maintaining consistent media flow rate
Knob adjustment	Yes	Yes	Easy to use and more compact than other types of handles
<b>Maintenance</b>			
Cleanout port	No	Yes	Clear obstructions without removing or disassembling valve
Access necessary for maintenance	Top & Bottom	Bottom	Easy access and fewer components shortens time to rebuild
Body bolt	5/16" x 3 1/4"	3/8" x 1"	Simplifies disassembly and reassembly



[www.AxxiomMfg.com](http://www.AxxiomMfg.com)

**Axxiom Manufacturing, Inc.**  
1.800.231.2085 • 281.431.0581

11927 South Highway 6 • Fresno, TX 77545 USA

© 2007 Axxiom Manufacturing Co. Inc.  
Axxiom, MV, MV2, and Microvalve are trademarks and Schmidt, the stylized "S", Combovalve and Thompson Valve are registered trademarks of Axxiom Manufacturing Co. Inc. All rights reserved.

