

PCWI Magnetic Thermometers

Climatic Condition Testing

PCWI International are leaders in the manufacture, certification and distribution of specialist measuring instruments relevant to the metals construction and coating industries.



Magnetic Thermometers

PTC312 & PTC314

Applications

Measurement of Temperature in °C

Features

Built in magnet to attach to substrate Specifications

Range

PTC312CRR: -20°C to +120°C PTC314CRR: +10°C to +400°C



Dewpoint Calculation Booklet


Applications

Conversion of Wet & Dry bulb readings into Relative Humidity and Dewpoint

Specifications

Range: -10°C to +50°C

within 1% of Standard Relative Humidity Scales Accuracy:



Whirling Hygrometer

Applications

Measurement of wet & dry bulb temperature in °C

Specifications

-5°C to +50°C Range:

Operation

Held by handle and spun for 15 to 30 seconds, facing any air flow. When the wet bulb reads a constant temperature, dew point and relative humidity can be determined by reference to a Dewpoint Calculation Booklet.



Certification of Temperature Available

PCWI International Pty Ltd

13 Alhambra Avenue CARDIFF NSW 2285 Ph: (02) 4954 3900 • Fax (02) 4954 3999

email: sales@pcwi.com.au • http://www.pcwi.com.au

Copyright 2016 Burwell Technologies