

PCWI Surface Profile / Dial Gauges

Surface Profile

PCWI International are leaders in the manufacture, certification and distribution of specialist measuring instruments relevant to the metals construction and coating industries.



PCWI Surface Profile Needle Gauges

Application

Measurement of Surface Profile and Pitting.
Requires a small flat area for measurement.
The special foot and needle ensures it meets the requirements of AS3894 Series.

Specifications

Range:
Analogue: 0 to 1000 μ m
Digital: 0 to 5000 μ m
Accuracy: \pm 2 μ m

Dial face diameter:
Analogue: 50mm
Digital: 42mm



1070

PCWI Dial Gauge

Application


Permanent record of peak-to-valley height of profile after sand, grit or shot blasting.

Specifications

Range: 0 to 10mm
Accuracy: 1 μ m
Resolution: 0.001
Dial face diameter: 55mm

Testex Tape

Tests per tape roll: 50
Range
Coarse Tape: 20 to 50 μ m
X Coarse Tape: 40 to 115 μ m



0706

PCWI International Pty Ltd

13 Alhambra Avenue CARDIFF NSW 2285
Ph: (02) 4954 3900 • Fax (02) 4954 3999
email: sales@pcwi.com.au • <http://www.pcwi.com.au>