

Quality Despatch Certificate

GMA Mining Australia



PRODUCT: GMA SpeedBlast™

BATCH NUMBER: 26-30-6D-A-130-Y

TYPICAL MINERAL COMPOSITION

Garnet (Almandine)	97 – 98%
Ilmenite	<3.5%
Zircon	0.20%
Quartz (Free Silica)	<0.1%
Others	0.25%

TYPICAL CHEMICAL COMPOSITION

SiO ₂	36.60%
Al ₂ O ₃	20.80%
Fe ₂ O ₃	34.50%
TiO ₂	1.30%
MnO	0.92%
CaO	1.77%
MgO	6.10%
Pb	<20ppm
Water Soluble Sulphate (SO ₄)	<10ppm
Free Calcium Carbonate (CaCO ₃)	<1.00%

TYPICAL RESULTS

Chloride (ISO Standard 11127-7)	Chloride Limit = 25ppm GMA Mining Australia products are tested in accordance with ISO 11127-7 with a chloride content of less than 25 parts per million and an average of 15 parts per million.
Average Result = 1.8 ppm	
Conductivity (ISO Standard 11127-6)	Conductivity Limit = 25 mS/m @ 20°C GMA Mining Australia products are tested in accordance with ISO 11127-6 with a conductivity content of less than 25 millisiemens per meter and an average of 12 millisiemens per meter
Average Result = 8.6 mS/m	

Date of issue 12/08/2026